

27

# PRECISION 1.25 VOLT MICROPOWER VOLTAGE REFERENCE

**ZRA125**

ISSUE 1 - OCTOBER 1995

## DEVICE DESCRIPTION

The ZRA125 uses a bandgap circuit design to achieve a precision micropower voltage reference of 1.25 volts. The device is available in small outline surface mount packages, ideal for applications where space saving is important, as well as packages for through hole requirements.

The ZRA125 design provides a stable voltage without an external capacitor and is stable with capacitive loads. The ZRA125 is recommended for operation between 50µA and 5mA and so is ideally suited to low power and battery powered applications.

Excellent performance is maintained to a suggested absolute maximum of 25mA, however the rugged design and 20 volt processing allows the reference to withstand transient effects and currents up to 200mA. Superior switching capability allows the device to reach stable operating conditions in only a few microseconds.


## FEATURES

- Small outline SOT23, SO8 and TO92 style packages
- No stabilising capacitor required
- Typical  $T_C$  30ppm/°C
- Typical slope resistance 0.65Ω
- ± 3%, 2% and 1% tolerance
- Industrial temperature range
- Operating current 50µA to 5mA
- Transient response, stable in less than 10µs
- Optional extended current range

## APPLICATIONS

- Battery powered and portable equipment.
- Metering and measurement systems.
- Instrumentation.
- Data acquisition systems.
- Precision power supplies.
- Test equipment.

## SCHEMATIC DIAGRAM



CONNECTION TABLE					
Pin	SO8	SOT23	E-LINE 3 pin	E-LINE 3 pin R	E-LINE 2 pin
1	N/C	-	-	G <sub>nd</sub>	G <sub>nd</sub>
2	N/C	G <sub>nd</sub>	V <sub>R</sub>	V <sub>R</sub>	V <sub>R</sub>
3	N/C	V <sub>R</sub>	G <sub>nd</sub>	-	-
4	G <sub>nd</sub>	-	-	-	-
5	N/C	-	-	-	-
6	N/C	-	-	-	-
7	N/C	-	-	-	-
8	V <sub>R</sub>	-	-	-	-
Pack	N8	F	A	R	Y
see Diagrams Page 1 - 8					

# ZRA125

## ABSOLUTE MAXIMUM RATING

Reverse Current	25mA
Forward Current	25mA
Operating Temperature	-40 to 85°C
Storage Temperature	-55 to 125°C

## Power Dissipation (T<sub>amb</sub>=25°C)

SOT23	330mW
E-line, 3 pin (TO92)	500mW
E-line, 2 pin (TO92)	500mW
SO8	625mW


## ELECTRICAL CHARACTERISTICS

TEST CONDITIONS (Unless otherwise stated) T<sub>amb</sub>=25°C

SYMBOL	PARAMETER	CONDITIONS	LIMITS			TOL. %	UNITS
			MIN	TYP	MAX		
V <sub>R</sub>	Reverse Breakdown Voltage	I <sub>R</sub> =150μA	1.228 1.225 1.21	1.24 1.25 1.25	1.252 1.275 1.29	1 2 3	V
I <sub>MIN</sub>	Minimum Operating Current			30	50		μA
I <sub>R</sub>	Recommended Operating Current		0.05		5		mA
T <sub>C</sub> †	Average Reverse Breakdown Voltage Temp. Co.	I <sub>R(min)</sub> to I <sub>R(max)</sub>		30	90		ppm/°C
R <sub>S</sub> §	Slope Resistance			0.65	2		Ω
Z <sub>R</sub>	Reverse Dynamic Impedance	I <sub>R</sub> = 1mA f = 100Hz I <sub>AC</sub> = 0.1 I <sub>R</sub>		0.5	1		Ω
E <sub>N</sub>	Wideband Noise Voltage	I <sub>R</sub> = 150μA f = 100Hz to 10kHz		70			μA(max)

$$† T_C = \frac{V_R \text{ Change} \times 1000000}{V_R \times \text{Temperature Change}}$$

$$§ R_S = \frac{V_R \text{ Change } (I_R(\text{min}) \text{ to } I_R(\text{max}))}{I_R(\text{max}) - I_R(\text{min})}$$



Reverse Characteristics

# ZRA125

## TYPICAL CHARACTERISTICS

